

USAGE CHART

Kleerstrip ImpacDors® are designed for durability.

Offering a full range of traffic doors, Kleerstrip's product line is available in clear, rigid and flexible doors suitable for forklift or pedestrian traffic.

Our Impactdor usage chart below can help guide you to the right door for your application. Please call an Aleco representative with any questions, 1-800-599-7004.



	Clear-Valu	Optima	Supra	Magna	FS-250	FS-500	RD-175	FD-175	HD-175	XHD-175	AIS-175	AIS-XHD	Steel-Lite™
Industrial/Commercial													
Heavy Forklift (30 cycles per hour)	NR	P	P	P	NR	NR	NR	NR	NR	NR	S	P	NR
Medium Forklift (15-30 cycles per hour)	NR	P	P	P	NR	NR	NR	NR	S	S	P	P	S
Light Forklift (15 or less cycles per hour)	NR	P	P	P	NR	NR	NR	S	P	P	P	P	P
Motorized Pallet Jack	NR	P	P	P	NR	NR	S	P	P	P	P	P	P
Hand Pallet	S	P	P	P	S	NR	P	P	P	P	P	P	P
Carts & Personnel	P	P	S	S	P	P	P	P	P	P	S	S	S
Washdown USDA*	P	P	S	S	S	S	P	S	P	P	S	S	S
Cold Storage above 32° F	P	P	P	P	NR	NR	P	P	P	P	P	P	S
Cold Storage below 32° F	P(4)	NR	NR	S(4)	NR	NR	S(2)	S(2)	S(1)	S(3)	P(2)	P(2)	S(1)
Retail/Supermarket/Restaurant													
Primary Sales - Stock & Palletized Loads	NR	NR	NR	NR	S	S	S	P	P	P	S	S	NR
Secondary Sales - Stock (Stock Cars/Personnel)	NR	NR	NR	NR	P	P	P	P	P	S	S	S	NR
Prep Areas (Cart & Personnel)	NR	NR	NR	NR	P	P	P	P	P	S	NR	NR	NR
Loading Dock	NR	NR	NR	NR	NR	NR	S-NDS	S-NDS	P-NDS	P	P-NDS	P-NDS	P
Stock Cooler	P	NR	NR	NR	NR	NR	P	P	P	S	S	S	NR
Kitchen to Dining	NR	NR	NR	NR	P	P	P	P	P	NR	NR	NR	NR

* Please specify washdown or USDA applications when ordering; optional features may be necessary to accommodate USDA/ Washdown requirements.

P: Primary Application
S: Secondary Application
NR: Not Recommended
P-NDS: No Direct Sunlight
S-NDS: No Direct Sunlight

(1) Can be used down to minus 40°F.
(2) Do not use below minus 20°F.
(3) Can be used down to minus 40°F with metal skin and down to minus 20°F with ABS skin.
(4) Can be used down to minus 40°F with low temp material